


Aquadive KTP 300 submersible pump resistant, with float switch, 10 m



Article information

Item no.: 28840C
GTIN: 4026092093634
Price group: 20

Advantages

- Multi-vane vortex impeller for maximum reliability
- Longitudinally watertight potted connection cable
- Integrated shallow extraction

Description

KTP 300 submersible pump with float switch, with non-return flap, pivoted connection, removable intake cage; the water level can be lowered to 8 mm.

Variant

Resistant:

Resistant to saline media, wastewater from water softening systems and wastewater containing condensate from heating systems

Rim width:

Float switch

Backwater protection:

integrated

General characteristics

Type of wastewater:

without sewage

Dimensions

Net weight:

4,45 kg

Gross weight:

4,81 kg

Width:

390 mm

Height:

216 mm

Length:

275 mm

Packaging dimension:

width

Packaging dimension:

height

Packaging dimension:	length
Wastewater contents	
Pressure pipe connection:	R 1 "
Pumping device	
Pump control:	KTP 300 resistant
Number of pumps:	1
Weight:	4 kg
Connection type:	Schuko (earthed contact) 2-pin
Rated current:	1,9 A
Length of mains cable for pump:	10 m
Self-diagnosis system (SDS):	I
Insulation class:	F
Protection class control unit:	IP 68
Max. temperature (permanent) of conveyed material:	40 °C
Hot water resistance for a short time (2 min):	80 °C
Max. pumping height:	6 m
Speed:	2800 U/min
Power P1:	0,34 kW
Power P2:	0,21 kW
Operating mode:	S1
Type of fuse required (electrical protection):	C 16 A
Type of pump connection cable:	H07RN-F 3G 1.5 mm ²
Impeller type:	Multi-vane impeller
Free passage:	10 mm
Control	
Type of level measurement:	mechanical
Mains frequency:	50 Hz
Operating voltage:	230 V
Connection type:	Schuko (earthed contact) 2-pin