


## Submersible pump Aquadive GTF1000 with float switch, 10 m



### Article information

Item no.: 28860  
 GTIN: 4026092044513  
 Price group: 20

### Advantages

- Multi-vane vortex impeller for maximum reliability
- Longitudinally watertight potted connection cable
- Integrated shallow extraction

### Description

Submersible pump for faecal-free wastewater, type KTP 1000, new designation: **GTF 1000**

Variant  
 Pump control: **Float switch**

General characteristics  
 Material: **Polymer**  
 Standard: **EN 12050-2**  
 Type of wastewater: **without sewage**  
 Cable length: **10 m**

Dimensions  
 Net weight: **10 kg**  
 Gross weight: **11,19 kg**  
 Length: **195 mm**  
 Width: **195 mm**  
 Height: **290 mm**  
 Packaging dimension: **length**  
 Packaging dimension: **width**  
 Packaging dimension: **height**

Wastewater contents

Pressure pipe connection:	R 1 ¼"
Pumping device	
Pump:	GTF 1000
Number of pumps:	1
Weight, pump:	10 kg
Connection type:	coded plug
Rated current:	5,6 A
Length of mains cable for pump:	10 m
Protection class:	I
Insulation class:	F
Cos phi - power factor:	0,97
Protection class (pump):	IP 68 (3m)
Temperature monitoring:	integrated
Max. temperature (permanent) of conveyed material:	40 °C
Hot water resistance for a short time (2 min):	80 °C
Max. pumping height:	10 m
Speed:	2700 U/min
Power P1:	1,3 kW
Power P2:	0,75 kW
Operating mode:	S3 - 50 %
Type of fuse required (electrical protection):	C 16 A
Type of pump connection cable:	H07RN-F 3G 1.5 mm <sup>2</sup>
Impeller type:	Multi-vane impeller
Free passage:	10 mm
Control	
Type of level measurement:	mechanical
Mains frequency:	50 Hz
Operating voltage:	230 V
Connection type:	coded plug
Rated current:	5,6 A