


## Submersible pump Aquadive GTF1000 resistant, with float switch, 10 m



### Article information

Item no.: 28860C  
GTIN: 4026092093771  
Price group: 20

### Advantages

- Multi-vane vortex impeller for maximum reliability
- Longitudinally watertight potted connection cable
- Integrated shallow extraction

### Description

Submersible pump for faecal-free wastewater

Variant

Resistant:

Resistant to saline media, wastewater from water softening systems and wastewater containing condensate from heating systems

Rim width:

Float switch

General characteristics

Type of wastewater:

without sewage

Dimensions

Net weight:

10 kg

Gross weight:

10,5 kg

Width:

195 mm

Height:

290 mm

Length:

195 mm

Packaging dimension:

width

Packaging dimension:

height

Packaging dimension:

length

Wastewater contents	
Pressure pipe connection:	R 1 ¼ "
Pumping device	
Pump control:	GTF 1000 resistant
Weight:	10 kg
Connection type:	coded plug
Rated current:	5,6 A
Length of mains cable for pump:	10 m
Self-diagnosis system (SDS):	I
Insulation class:	F
Protection class control unit:	IP 68 (3m)
Max. temperature (permanent) of conveyed material:	40 °C
Hot water resistance for a short time (2 min):	80 °C
Max. pumping height:	10 m
Speed:	2700 U/min
Power P1:	1,3 kW
Power P2:	0,75 kW
Operating mode:	S3 - 50 %
Type of fuse required (electrical protection):	C 16 A
Type of pump connection cable:	H07RN-F 3G 1.5 mm <sup>2</sup>
Impeller type:	Multi-vane impeller
Free passage:	10 mm
Control	
Type of level measurement:	mechanical
Mains frequency:	50 Hz
Operating voltage:	230 V
Connection type:	coded plug