

## Submers. pump Aquadive GTF 1700 resistant, with float switch, 10 m, 230 V

### Article information

Item no.: 28882C  
GTIN: 4026092113684  
Price group: 20

### Description

Submersible pump Aquadive GTF1700, resistant, with float switch, 10m

The submersible pump for maximum operational safety, with longitudinally watertight moulded connection line and removable intake cage

#### Variant

Resistant: Resistant to waste water containing salt, softener and condensate  
Pump control: Float switch

#### General characteristics

Material: Polymer, Stainless steel  
Standard: EN 12050-2  
Type of wastewater: without sewage  
Cable length: 10 m

#### Dimensions

Length: 240 mm  
Width: 200 mm  
Height: 377 mm

#### Tank/drain body

Pressure pipe connection: R 1 ¼"

#### Pumping device

Pump: GTF 1700  
Weight, pump: 13,9 kg  
Connection type: coded plug  
Operating voltage: 230 V  
Protection class: I  
Insulation class: F  
Cos phi - power factor: 0,97  
Protection class (pump): IP 68 (3m)  
Temperature monitoring: integrated  
Max. temperature (permanent) of conveyed material: 40 °C

Hot water resistance for a short time (2 min):	80 °C
Max. pumping height:	13 m
Speed:	2850 U/min
Power P1:	1,6 kW
Power P2:	1 kW
Operating mode:	S3 - 50 %
Type of pump connection cable:	H07RN-F 3G 1.5 mm <sup>2</sup>
Impeller type:	Multi-vane impeller
Free passage:	30 mm
Type of fuse required (pump):	C 16 A
Length of mains cable for pump:	10 m
Rated current:	7,3 A
Control	
Operating voltage:	230 V
Connection type:	coded plug
Mains frequency:	50 Hz