


Universal Plus basement drain vertical, with odour trap





Article information

Item no.: 29103 GTIN: 4026092096963 Price group: 10

Advantages

- Sustainable due to use of recycled material
- Inlets above the floor slab, no penetration required
- Vertical outlet for easy installation and easy access to the main drainage pipe

Description

In combination with an upper section, the polymer Universal Plus drain body is used for drainage of non-faecal wastewater and is equipped with a removable odour trap and a sludge bucket. Including temporary protective cover. The drain is pressurewaterproof up to 0.6 bar (MFPA Leipzig tested) and radon-tight (IAF Radioökologie GmbH tested).

Variant Contents of sludge trap: Waterproof flange: Sealing water height:	yes without 60 mm
General characteristics	
Colour:	black
Standard:	EN 1253
Nominal size (DN):	100
Type of wastewater:	without sewage
Installation situation:	floor slab installation
Dimensions	
Net weight:	1,73 kg
Gross weight:	2,22 kg
Diameter:	235 mm
Cutout dimension, width:	310 mm



Cutout dimension, length: Vertical adjustment: Height: Packaging dimension: Packaging dimension: Packaging dimension:

Tank/drain body Outlet nominal size (OD): Outlet nominal size (DN): System:

Coverage features Contents of sludge trap: Odour trap: 310 mm vertically adjustable upper section 270 mm width height length

110 mm 100 vertical

yes included