

Practicus basement drain DN 100, Black grating, Vertical outlet



Article information

Item no.: 34102
 GTIN: 4026092047705
 Price group: 10

Advantages

- Vertically adjustable upper section
- Suitable for floor slab installation

Description

The Practicus basement drain is made of polymer and is suitable for floor slab installation. The upper section with slotted grating is vertically adjustable.

Variant

Contents of sludge trap:	yes
Discharge rate (l/s) with 10 mm backwater:	1,1
Discharge rate (l/s) with 20 mm backwater:	1,8

General characteristics

Standard:	EN 1253-2
Nominal size (DN):	100
Outer diameter (OD):	110 mm

Dimensions

Net weight:	1,33 kg
Gross weight:	1,55 kg
Cutout dimension, width:	180 mm
Cutout dimension, length:	180 mm
Installation depth:	221 - 277 mm
Vertical adjustment:	vertically adjustable upper section
Width:	150 mm
Length:	150 mm
Packaging dimension:	width
Packaging dimension:	height
Packaging dimension:	length

Tank/drain body

Number of outlets:	1
Material of drain body:	Polymer
System:	vertical

Coverage features

Type of cover:	Slotted cover
Cover material:	Polymer
Colour of cover:	black
Width of cover:	138 mm
Length of cover:	138 mm
Frame material:	Polymer
Cover locking:	placed
Load class:	K 3 (EN 1253-1)
Shape of upper section:	square
Upper section material:	Polymer
Contents of sludge trap:	yes
Odour trap:	no