

Variofix Classic bathroom drain DN 50, horiz., Design grating Oval, L 15



Article information

Item no.: 40150.54 GTIN: 4026092033975 Price group: 10

Advantages

- Odour trap height: 50 mm
- Lip seal fixed on the drain body
- Side adjustable cover

Description

The Classic bathroom drain is suitable for indoor floor drainage. The drain made of ABS is equipped with a telescopic, height-adjustable upper section made of polymer, a removable odour trap as well as a secure, reliably installed seal. Including upper section for combined waterproofing for alternative WP layer.

Variant	
Waterproofing layer on the upper section:	Enclosed sealing collar to be glued (bd) according to DIN 18534
Water exposure class in accordance to DIN	W3-I
18534-1 (up to and including):	
Sealing water height:	50 mm
Discharge rate (l/s) with 20 mm threshold:	0,8
General characteristics	
Standard:	EN 1253-1
Nominal size (DN):	50
Outer diameter (OD):	50 mm
Odour trap:	included
Dimensions	
Vertical adjustment:	45 - 110 mm
Net weight:	1,44 kg
Gross weight:	2,07 kg
Cutout dimension, width:	180 mm
Cutout dimension, length:	220 mm
Type of height adjustability:	vertically adjustable upper section
Length:	312 mm
Width:	312 mm
Packaging dimension:	length
Packaging dimension:	width



Packaging dimension:

Tank/drain body Number of outlets: Material of drain body: Socket version:

Coverage features Type of cover: Cover material: Colour of cover: Width of cover: Length of cover: Surface: Frame material: Locking: Load class: Grating design: Rim width: Rim length: Shape of upper section: Upper section material: height

1 ABS lateral

Design cover Stainless steel 14301 silver 120 mm 120 mm ground Stainless steel 14301 Lock & Lift L 15 (EN 1253-1) Oval 132 mm 132 mm square ABS