

Variofix Classic bathroom drain Gl fl., DN 50, horiz., slot grat., K3



Article information

Item no.: 40159.50 GTIN: 4026092029329 Price group: 10

Advantages

- Odour trap height: 50 mm
- Lip seal fixed on the drain body
- Side adjustable cover

Description

The Classic bathroom drain is suitable for indoor floor drainage. The drain made of ABS is equipped with a telescopic, height-adjustable upper section made of polymer, a removable odour trap as well as a secure, reliably installed seal. Including upper section for combined waterproofing for alternative WP layer.

Variant Waterproofing layer on the upper section:	Enclosed sealing collar to be glued (bd) according to DIN 18534
Waterproofing layer on the drain body: Water supply: Sealing water height:	Adhesive flange (suitable for moisture barriers) W3-I 50 mm
Discharge rate (l/s) with 20 mm backwater:	0,8
General characteristics	
Standard:	EN 1253-1
Nominal size (DN):	50
Outer diameter (OD):	50 mm
Dimensions	
Vertical adjustment:	55 - 120 mm
Net weight:	1,41 kg
Gross weight:	2,04 kg
Cutout dimension, width:	350 mm
Cutout dimension, length:	350 mm
Vertical adjustment:	vertically adjustable upper section
Width:	332 mm
Length:	332 mm
Packaging dimension:	width
Packaging dimension:	height
Packaging dimension:	length



Tank/drain body Number of outlets: Material of drain body: System:

Coverage features Type of cover: Cover material: Colour of cover: Width of cover: Length of cover: Surface: Frame material: Cover locking: Load class: Rim length: Rim material: Shape of upper section: Upper section material: Odour trap: 1 ABS lateral

Slotted cover Stainless steel 14301 silver 95 mm 95 mm Polished SST ABS placed K 3 (EN 1253-1) 132 mm 132 mm square ABS included