

Variofix Classic bathroom drain DN 70, horiz., Slotted grating, L 15



Article information

Item no.: 40170.51 GTIN: 4026092029343

Price group: 10

Advantages

Odour trap height: 50 mmLip seal fixed on the drain body

• Side adjustable cover

Description

The Classic bathroom drain is suitable for indoor floor drainage. The drain made of ABS is equipped with a telescopic, height-adjustable upper section made of polymer, a removable odour trap as well as a secure, reliably installed seal. Including upper section for combined waterproofing for alternative WP layer.

Variant

Waterproofing layer on the upper section: Enclosed sealing collar to be glued (bd) according to

DIN 18534

W3-I

Water exposure class in accordance to DIN

18534-1 (up to and including):

Sealing water height: 50 mm Discharge rate (l/s) with 20 mm threshold: 0,8

General characteristics

Standard: EN 1253-1

Nominal size (DN): 70
Outer diameter (OD): 75 mm
Odour trap: included

Dimensions

Vertical adjustment: 45 - 110 mm
Net weight: 1,35 kg
Gross weight: 1,98 kg
Cutout dimension, width: 180 mm
Cutout dimension, length: 220 mm

Type of height adjustability: vertically adjustable upper section

Length: 312 mm
Width: 312 mm
Packaging dimension: length
Packaging dimension: width
Packaging dimension: height



Tank/drain body

Number of outlets: 1
Material of drain body: ABS
Socket version: lateral

Coverage features

Type of cover: Slotted cover

Cover material: Stainless steel 14301

Colour of cover: silver
Width of cover: 138 mm
Length of cover: 138 mm
Surface: Polished SST

Frame material: Stainless steel 14301

Locking: placed

Load class: L 15 (EN 1253-1)

Rim width: 150 mm
Rim length: 150 mm
Shape of upper section: square
Upper section material: ABS