

## Variofix Classic bathroom drain Gl fl., DN 50, vert., slot grat., K3



## **Article information**

Item no.: 40259.50 GTIN: 4026092029503

Price group: 10

## **Advantages**

Odour trap height: 50 mmLip seal fixed on the drain body

• Side adjustable cover

## **Description**

The Classic bathroom drain is suitable for indoor floor drainage. The drain made of ABS is equipped with a telescopic, height-adjustable upper section made of polymer, a removable odour trap as well as a secure, reliably installed seal. Including upper section for combined waterproofing for alternative WP layer.

Variant

Waterproofing layer on the upper section: Enclosed sealing collar to be glued (bd) according to

DIN 18534

Waterproofing layer on the drain body:

Adhesive flange (suitable for moisture barriers)

Water exposure class in accordance to DIN W3-

18534-1 (up to and including):

Sealing water height: 50 mm Discharge rate (l/s) with 20 mm threshold: 0,8

General characteristics

Standard:EN 1253-1Nominal size (DN):50Outer diameter (OD):50 mmOdour trap:included

**Dimensions** 

Vertical adjustment:55 - 120 mmNet weight:2,05 kgGross weight:2,68 kgCutout dimension, width:350 mmCutout dimension, length:350 mm

Type of height adjustability: vertically adjustable upper section

Length: 332 mm
Width: 332 mm
Packaging dimension: length
Packaging dimension: width



Packaging dimension: height

Tank/drain body

Number of outlets: 1
Material of drain body: ABS
Socket version: vertical

Coverage features

Type of cover: Slotted cover

Cover material: Stainless steel 14301

Colour of cover: silver
Width of cover: 95 mm
Length of cover: 95 mm
Surface: Polished SST

Frame material: ABS Locking: placed

Load class: K 3 (EN 1253-1)

Rim width: 132 mm
Rim length: 132 mm
Shape of upper section: square
Upper section material: ABS