


## The Ultraflat 54 floor drain DN 40, enclWPM, Slotted grating



### Article information

Item no.: 44740.20  
 GTIN: 4026092080788  
 Price group: 10

### Advantages

- including removable odour trap in the upper section
- Low installation depth
- Scientifically confirmed sound insulation effect

### Description

The Ultraflat 54 floor drain is suitable for indoor floor drainage. The polymer drain is equipped with a removable odour trap in the upper section.

#### Variant

System:	125
Seepage opening:	optional
Waterproofing layer on the drain body:	Enclosed sealing collar to be glued (bd) according to DIN 18534
Water exposure class in accordance to DIN 18534-1 (up to and including):	W2-I
Sealing water height:	22 mm

#### General characteristics

Nominal size (DN):	40
Outer diameter (OD):	40 mm
ATEX:	no

#### Dimensions

Vertical adjustment:	63 - 116 mm
Net weight:	0,46 kg
Gross weight:	0,67 kg
Type of height adjustability:	vertically adjustable upper section
Length:	246 mm
Width:	200 mm
Height:	54 mm
Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height

Tank/drain body

Number of outlets:	1
Material of drain body:	ABS
Coverage features	
Type of cover:	Slotted cover
Cover material:	Stainless steel 14301
Colour of cover:	silver
Width of cover:	120 mm
Height of cover:	16 mm
Length of cover:	120 mm
Surface:	Polished SST
Frame material:	ABS
Locking:	unlocked
Load class:	K 3 (EN 1253-1)
Rim width:	130 mm
Rim length:	130 mm
Shape of upper section:	square
Upper section material:	ABS
Odour trap:	included