


The Ultraflat 54 floor drain DN 40, WaD, Slotted grating





Article information

Item no.: 44740.20M GTIN: 4026092080757

Price group: 10

Advantages

- including removable odour trap in the upper section
- Low installation depth
- Scientifically confirmed sound insulation effect

Description

The Ultraflat 54 floor drain is suitable for indoor floor drainage. The polymer drain is equipped with a removable odour trap in the upper section.

Variant

System: 125 Seepage opening: optional

Waterproofing layer on the drain body: Factory-fitted sealing collar (WaD) according to DIN

18534 W3-I

Water exposure class in accordance to DIN

18534-1 (up to and including):

Sealing water height: 22 mm

General characteristics

Nominal size (DN): 40
Outer diameter (OD): 40 mm
ATEX: no

Dimensions

Vertical adjustment: 63 - 116 mm
Net weight: 0,69 kg
Gross weight: 0,77 kg

Type of height adjustability: vertically adjustable upper section

Length: 246 mm Width: 200 mm



Height: 54 mm
Packaging dimension: length
Packaging dimension: width
Packaging dimension: height

Tank/drain body

Number of outlets: 1
Material of drain body: ABS

Coverage features

Type of cover: Slotted cover

Cover material: Stainless steel 14301

Colour of cover:

Width of cover:

Height of cover:

Length of cover:

120 mm

16 mm

120 mm

Frame material:

ABS

Locking:

unlocked

Load class:

K 3 (EN 1253)

Load class: K 3 (EN 1253-1)
Slip resistance class: R9 according to DIN 51130; C according to DIN

51097

Rim width:130 mmRim length:130 mmShape of upper section:squareUpper section material:ABSOdour trap:included