



## The Ultraflat 54 floor drain DN 50, WaD, Slotted grating



### Article information

Item no.: 44750.20M  
 GTIN: 4026092080832  
 Price group: 10

### Advantages

- including removable odour trap in the upper section
- Low installation depth
- Scientifically confirmed sound insulation effect

### Description

The Ultraflat 54 floor drain is suitable for indoor floor drainage. The polymer drain is equipped with a removable odour trap in the upper section. Open seepage water opening, no flooding of the waterproofing level in the event of build-up.

Variant	
System:	125
Seepage opening:	optional
Waterproofing layer on the drain body:	Factory-fitted sealing collar (WaD) according to DIN 18534
Water exposure class in accordance to DIN 18534-1 (up to and including):	W3-I
Sealing water height:	22 mm
General characteristics	
Nominal size (DN):	50
Outer diameter (OD):	50 mm
Odour trap:	included
Sustainable:	through the use of recycled material
Dimensions	
Vertical adjustment:	63 - 116 mm
Net weight:	0,49 kg
Gross weight:	0,67 kg
Type of height adjustability:	vertically adjustable upper section

Length:	246 mm
Width:	200 mm
Height:	54 mm
Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height
Tank/drain body	
Number of outlets:	1
Material of drain body:	ABS
Coverage features	
Type of cover:	Slotted cover
Cover material:	Stainless steel 14301
Colour of cover:	silver
Width of cover:	120 mm
Height of cover:	16 mm
Length of cover:	120 mm
Frame material:	ABS
Locking:	unlocked
Load class:	K 3 (EN 1253-1)
Slip resistance class:	R9 according to DIN 51130; C according to DIN 51097
Rim width:	130 mm
Rim length:	130 mm
Shape of upper section:	square
Upper section material:	ABS