


The Ultraflat 54 floor drain DN 50, WaD, Design cover, L&L, Megastop



Article information

Item no.: 44750.66M
 GTIN: 4026092080894
 Price group: 10

Advantages

- including removable odour trap in the upper section
- Low installation depth
- Scientifically confirmed sound insulation effect

Description

The Ultraflat 54 floor drain is suitable for indoor floor drainage. The polymer drain is equipped with a removable odour trap in the upper section.

Variant

System:	125
Seepage opening:	optional
Backflow preventer:	up to 0.1 bar
Waterproofing layer on the drain body:	Factory-fitted sealing collar (WaD) according to DIN 18534
Water exposure class in accordance to DIN 18534-1 (up to and including):	W3-I
Sealing water height:	10 mm

General characteristics

Nominal size (DN):	50
Outer diameter (OD):	50 mm

Dimensions

Vertical adjustment:	70 - 121 mm
Net weight:	0,65 kg
Gross weight:	1,1 kg
Vertical adjustment:	vertically adjustable upper section

Length:	246 mm
Width:	200 mm
Height:	54 mm
Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height
Tank/drain body	
Number of outlets:	1
Material of drain body:	ABS
Coverage features	
Type of cover:	Design cover
Cover material:	Stainless steel 14301
Colour of cover:	silver
Width of cover:	120 mm
Height of cover:	16 mm
Length of cover:	120 mm
Surface:	ground
Frame material:	Stainless steel 14301
Locking:	Lock & Lift
Load class:	L 15 (EN 1253-1)
Grating design:	Kessel
Slip resistance class:	R9 according to DIN 51130; C according to DIN 51097
Rim width:	132 mm
Rim length:	132 mm
Shape of upper section:	square
Upper section material:	ABS
Odour trap:	Megastop