


Practicus floor/roof drain DN 100, horiz, Waterpr layer, Des grate





Article information

Item no.: 45110.53 GTIN: 4026092052815 Price group: 10

Advantages

- Hygiene: hygienic, absolutely corrosion-free and durable material
- Sound insulation: outstanding sound insulation effect confirmed by the Fraunhofer Institute

Description

The Practicus floor drain is used for point drainage and is equipped with a connection flange as well as a removable odour trap, a lip seal and a temporary protective cover. Including telescopic height-adjustable upper section made of ABS. The drain meets particular sound insulation requirements in accordance with the measurements of the Fraunhofer Institute in Stuttgart. The outlet socket is suitable for connection to SML cast iron pipes. With connection option for equipotential bonding.

Variant	
System:	125
Waterproofing layer on the upper section:	Enclosed sealing collar to be glued (bd) according to DIN 18534
Waterproofing layer on the drain body:	Connection flange
Sealing water height:	50 mm
Discharge rate (l/s) with 20 mm backwater:	1,6
General characteristics	
Standard:	EN 1253-1
Nominal size (DN):	100
Outer diameter (OD):	110 mm
Dimensions Vertical adjustment: Net weight:	10 - 23 mm 2,62 kg



Gross weight: Vertical adjustment: Packaging dimension: Packaging dimension: Packaging dimension:

Tank/drain body Number of outlets: Connection inlet/outlet sockets:

Material of drain body: System:

Coverage features Type of cover: Cover material: Colour of cover: Width of cover: Length of cover: Surface: Frame material: Cover locking: Load class: Grating colour: Slip resistance class:

Rim length: Rim material: Upper section: Shape of upper section: Upper section material: Odour trap: 3,38 kg vertically adjustable upper section width height length

1 The outlet spigot is suitable for connection to SML pipes. PP lateral

Design cover Stainless steel 14301 silver 120 mm 120 mm ground Stainless steel 14301 Lock & Lift L 15 (EN 1253-1) Kessel R9 according to DIN 51130; C according to DIN 51097 132 mm 132 mm adjustable in three dimensions square ABS included