

Practicus drain body Press. fl., DN 100, Horizontal outlet



Article information

Item no.: 45119

GTIN: 4026092033791

Price group: 10

Advantages

- Hygiene: hygienic, absolutely corrosion-free and durable material
- absolutely corrosion-free and durable material

Description

In combination with an upper section, the Practicus polymer drain body is used for point drainage and is equipped with a removable odour trap and a temporary protective cover. The drain meets particular sound insulation requirements in accordance with the measurements of the Fraunhofer Institute in Stuttgart.

Variant

System: 125

Waterproofing layer on the upper section: Enclosed sealing collar to be glued (bd) according to

DIN 18534

Waterproofing layer on the drain body: Press sealing flange (suitable for creating

watertight seals)

Sealing water height: 50 mm

General characteristics

Nominal size (DN): 100 Outer diameter (OD): 110 mm

Dimensions

Net weight:1,83 kgGross weight:2,12 kgDiameter:273 mmHeight:147 mmPackaging dimension:lengthPackaging dimension:widthPackaging dimension:height

Tank/drain body

Number of outlets: 1

Connection inlet/outlet sockets: The outlet spigot is suitable for connection to SML

pipes.

Material of drain body: PP



| Socket version: | lateral |
|-----------------|---------|
|-----------------|---------|

Coverage features

Odour trap: included