

Practicus drain body Press. fl., DN 50, Vertical outlet





Article information

Item no.: 45259 GTIN: 4026092033807 Price group: 10

Advantages

- Hygiene: hygienic, absolutely corrosion-free and durable material
- absolutely corrosion-free and durable material
- Fire protection: combinable with the Fire-Kit for fire and smoke protection

Description

In combination with an upper section, the Practicus polymer drain body is used for point drainage and is equipped with a removable odour trap and a temporary protective cover. The drain meets particular sound insulation requirements in accordance with the measurements of the Fraunhofer Institute in Stuttgart.

Variant System: Waterproofing layer on the upper section:	125 Enclosed sealing collar to be glued (bd) according to DIN 18534
Waterproofing layer on the drain body:	Press sealing flange (suitable for creating watertight seals)
Sealing water height:	50 mm
General characteristics	
Nominal size (DN):	50
Outer diameter (OD):	50 mm
Approval:	Z-19.53-2414,Z-19.53-2414_V,Z-19.17-1719,Z-19.17-17 19_V
Odour trap:	included
Dimensions	
Net weight:	1,77 kg
Gross weight:	2,06 kg



Diameter: Height: Packaging dimension: Packaging dimension: Packaging dimension:

Tank/drain body Number of outlets: Material of drain body: Socket version: 273 mm 207 mm length width height

1 PP vertical