

Practicus drain body Press. fl., DN 70, Vertical outlet



Article information

Item no.: 45279 GTIN: 4026092033814 Price group: 10

Advantages

- Hygiene: hygienic, absolutely corrosion-free and durable material
- absolutely corrosion-free and durable material
- Fire protection: combinable with the Fire-Kit for fire and smoke protection

Description

In combination with an upper section, the Practicus polymer drain body is used for point drainage and is equipped with a removable odour trap and a temporary protective cover. The drain meets particular sound insulation requirements in accordance with the measurements of the Fraunhofer Institute in Stuttgart.

Svstem: 125 Waterproofing layer on the upper section: Enclosed sealing collar to be glued (bd) according to DIN 18534 Waterproofing layer on the drain body: Press sealing flange (suitable for creating watertight seals) Sealing water height: 50 mm General characteristics 70 Nominal size (DN): 75 mm Outer diameter (OD): Inlet max. scoring (DN): Z-19.53-2414, Z-19.17-1719 purchasable by service partner: No Dimensions Net weight: 1,1 kg Gross weight: 2,04 kg 273 mm Diameter: Height: 217 mm Packaging dimension: length Packaging dimension: width Packaging dimension: height

Tank/drain body

Variant



Number of outlets: Material of drain body: System:

Coverage features Odour trap: 1 PP vertical

included