

Shower channel Linearis Compact L: 950 mm, DN50, enclWPM, 304SSTcov, K3



Article information

Item no.: 45600.65 GTIN: 4026092046104 Price group: 10

Advantages

- Individual design with reversible stainless steel insert
- Low installation depth
- Highest fire protection standards

Description

The Linearis Compact shower channel with welded on drain body made of ABS is suitable for indoor linear drainage. If inserted upside down, the stainless steel insert can be tiled individually. Including prepared seepage water openings and odour trap.

Variant	
System:	125
SonicControl:	prepared
Waterproofing layer on the upper section:	Enclosed sealing collar to be glued (bd) according to
	DIN 18534
Water supply:	W2-I
Sealing water height:	22 mm
Discharge rate (l/s) with 10 mm backwater:	0,6
Discharge rate (l/s) with 20 mm backwater:	0,7
Discharge rate (l/s) without backwater:	0,5 mm
General characteristics	
Nominal size (DN):	50
Outer diameter (OD):	50 mm
Dimensions	
Net weight:	2,44 kg
Gross weight:	2,96 kg
Outer dimension, length:	1015 mm
Installation depth:	80 - 140 mm
Width:	191 mm
Height:	80 mm
Packaging dimension:	width
Packaging dimension:	height
Packaging dimension:	length



Tank/drain body Number of outlets: Material of drain body:

Coverage features Type of cover: Cover material: Colour of cover: Frame material: Cover locking: Load class: Grating colour: Rim length: Rim material: Max. flooring height: Upper section material: Odour trap: 1 ABS

Stainless steel cover Stainless steel 14301 silver Stainless steel 14301 placed K 3 (EN 1253-1) optionally tileable 66 mm 950 mm 15 mm ABS included