

Upper section, Linearis Compact L: 550 mm, Sys 100, 304 SST cover, K 3



Article information

Item no.: 47806S GTIN: 4026092079928 Price group: 10

Advantages

- Individual design with reversible stainless steel insert
- Low installation depth
- Ready-to-install complete set

Description

Used in combination with a drain body of the KESSEL 100 modular system, the Linearis Compact upper section is suitable for use as indoor linear drainage.

Variant	
System:	100
Seepage opening:	yes
Waterproofing layer on the upper section:	Enclosed sealing collar to be glued (bd) according to DIN 18534
Water exposure class in accordance to DIN 18534-1 (up to and including):	W3-I
Sealing water height:	50 mm
Discharge rate (l/s) with 10 mm threshold:	0,6
Discharge rate (l/s) without threshold:	0,5 mm
	0,3 mm
General characteristics	
Nominal size (DN):	100
Outer diameter (OD):	100 mm
Odour trap:	included
Dimensions	
Net weight:	1,56 kg
Gross weight:	1,97 kg
Outer dimension, length:	615 mm
Installation depth:	80 - 140 mm
Width:	136 mm
Height:	77 mm
Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height



Coverage features Type of cover: Cover material: Colour of cover: Frame material: Load class: Grating design: Rim width: Rim length: Upper section material:

Stainless steel cover Stainless steel 14301 silver Stainless steel 14301 K 3 (EN 1253-1) optionally tileable 66 mm 550 mm ABS