

Upper section, Linearis Compact L: 750mm, Sys 100, 304 SST cover, K 3



Article information

Item no.: 47808S GTIN: 4026092077818 Price group: 10

Advantages

- Individual design with reversible stainless steel insert
- Low installation depth
- Ready-to-install complete set

Description

Used in combination with a drain body of the KESSEL 100 modular system, the Linearis Compact upper section is suitable for use as indoor linear drainage.

| Variant | |
|--|---|
| System: | 100 |
| Seepage opening: | yes |
| Waterproofing layer on the upper section: | Enclosed sealing collar to be glued (bd) according to DIN 18534 |
| Water exposure class in accordance to DIN | W3-I |
| 18534-1 (up to and including): | FO |
| Sealing water height: | 50 mm |
| Discharge rate (l/s) with 10 mm threshold: | 0,6 |
| Discharge rate (l/s) without threshold: | 0,5 mm |
| General characteristics | |
| Nominal size (DN): | 100 |
| Outer diameter (OD): | 100 mm |
| Odour trap: | included |
| | Included |
| Dimensions | |
| Net weight: | 1,79 kg |
| Gross weight: | 2,55 kg |
| Outer dimension, length: | 815 mm |
| Installation depth: | 80 - 140 mm |
| Width: | 136 mm |
| Height: | 77 mm |
| Packaging dimension: | length |
| Packaging dimension: | width |
| Packaging dimension: | height |
| | 5 |



Coverage features Type of cover: Cover material: Colour of cover: Frame material: Load class: Grating design: Rim width: Rim length: Upper section material:

Stainless steel cover Stainless steel 14301 silver Stainless steel 14301 K 3 (EN 1253-1) optionally tileable 66 mm 750 mm ABS