


Scada LED wall drain w/cov, SST, 10 mm, fixed w/prf membrn



Article information

Item no.: 48003.42M
GTIN: 4026092079164
Discount group: 01

Advantages

- Flexible & convenient installation options
- Factory-mounted waterproofing membrane
- RGB strip light, for individually selectable colours

Description

The Scada wall drain is suitable for indoor floor drainage and provides connection options at the front, left and right-hand side.

Version:

Lighting:	LED
Odour trap:	included
Type of waterproofing layer:	Waterproofing layer
Waterproofing layer on the drain body:	Factory-fitted sealing collar (WaD) according to DIN 18534
Water exposure class in accordance to DIN 18534-1 (up to and including):	W3-I
Sealing water height:	22 mm

General characteristics:

Nominal size (DN):	50
Outer diameter (OD):	58

Dimensions:

Length:	362 mm
Width:	195 mm
Height:	353 mm

Tank:

Number of outlets: 1 ST

Drain body:

Material of drain body: ABS

Coverage features:

Type of cover: Scada drain cover
Grating design: Standard 74
Cover material: 304 stainless steel
Colour of cover: silver
Min. flooring height: 15 mm
Max. flooring height: 19 mm
null: 15 - 18 mm
Length: 312 mm
Height: 74 mm
Surface: Brushed SST
Locking: inserted

Grating:

Rim material: ABS
Shape of upper section: square
Upper section material: ABS
Discharge rate (l/s) with 20 mm backwater: 0.5 l/s