



Ecoguss project drain DN 70, vert., Variofix, Slotted cover



Article information

Item no.: 48478.51
GTIN: 4026092034378
Price group: 40

Advantages

- High-tech Ecoguss composite material
- Highest fire protection standards
- Scientifically confirmed sound protection effect

Description

The Ecoguss project drain with connection flange is used for point drainage and is equipped with a removable odour trap as well as a lip seal and a temporary protective cover. The recyclable composite material Ecoguss meets the highest noise protection requirements, is temperature-resistant, resistant to aggressive media, and has a permanently corrosion-free surface. It is also briefly flammable from 100 to 400 degrees Celsius. The outlet socket is suitable for connection to SML cast iron pipes. Separate equipotential bonding is not necessary.

Variant

System:

125

Waterproofing layer on the upper section:

Enclosed sealing collar to be glued (bd) according to DIN 18534

Waterproofing layer on the drain body:

Connection flange

Sealing water height:

50 mm

General characteristics

Standard:

EN 1253-1

Nominal size (DN):

70

Outer diameter (OD):

78 mm

Approval:

Z-19.53-2414,Z-19.53-2414_V,Z-19.17-1719,Z-19.17-1719_V

Odour trap:

included

Dimensions

Net weight:

2,99 kg

| | |
|-------------------------------|-------------------------------------|
| Gross weight: | 3,75 kg |
| Diameter: | 135 mm |
| Type of height adjustability: | vertically adjustable upper section |
| Length: | 135 mm |
| Width: | 135 mm |
| Packaging dimension: | length |
| Packaging dimension: | width |
| Packaging dimension: | height |

| | |
|-------------------------|-------------------|
| Tank/drain body | |
| Number of outlets: | 1 |
| Material of drain body: | Ecoguss resistant |
| Socket version: | vertical |

| | |
|-------------------------|--------------------------------|
| Coverage features | |
| Type of cover: | Slotted cover |
| Cover material: | Stainless steel 14301 |
| Colour of cover: | silver |
| Width of cover: | 138 mm |
| Length of cover: | 138 mm |
| Min. flooring height: | 10 mm |
| Frame material: | Stainless steel 14301 |
| Locking: | screwed |
| Load class: | K 3 (EN 1253-1) |
| Rim width: | 150 mm |
| Rim length: | 150 mm |
| Max. flooring height: | 17 mm |
| Upper section: | adjustable in three dimensions |
| Upper section material: | ABS |