


Ecoguss project drain DN 80, vertical, Design cover





Article information

Item no.: 48483.63 GTIN: 4026092053072 Price group: 40

Advantages

- High-tech Ecoguss composite material
- Highest fire protection standards
- Scientifically confirmed sound protection effect

Description

The Ecoguss project drain with connection flange is used for point drainage and is equipped with a removable odour trap as well as a lip seal and a temporary protective cover. The recyclable composite material Ecoguss meets the highest noise protection requirements, is temperature-resistant, resistant to aggressive media, and has a permanently corrosion-free surface. It is also briefly flammable from 100 to 400 degrees Celsius. The outlet socket is suitable for connection to SML cast iron pipes. Separate equipotential bonding is not necessary.

Variant	105
System:	125
Waterproofing layer on the upper section:	Connection flange
Waterproofing layer on the drain body:	Connection flange
Sealing water height:	50 mm
General characteristics	
Standard:	EN 1253-1
Nominal size (DN):	80
Outer diameter (OD):	83 mm
Approval:	Z-19.53-2414,Z-19.53-2414_V,Z-19.17-1719,Z-19.17-17
	19 V
Odour trap:	included
Dimensions	
	1.46.1/2
Net weight:	1,46 kg
Gross weight:	1,9 kg



Diameter: Type of height adjustability: Length: Width: Packaging dimension: Packaging dimension: Packaging dimension:

Tank/drain body Number of outlets: Material of drain body: Socket version:

Coverage features Type of cover: Cover material: Colour of cover: Width of cover: Height of cover: Length of cover: Surface: Frame material: Locking: Load class: Grating design: Slip resistance class:

Rim width: Rim length: Max. flooring height: Upper section: Shape of upper section: Upper section material: 135 mmvertically adjustable upper section135 mm135 mmlengthwidthheight

1 Ecoguss resistant vertical

Design cover Stainless steel 14301 silver 120 mm 16 mm 120 mm ground Stainless steel 14301 Lock & Lift L 15 (EN 1253-1) Kessel R9 according to DIN 51130; C according to DIN 51097 132 mm 132 mm 16 mm vertically adjustable square ABS