



Ecoguss project drain glu. flange DN 50, horizontal, Slotted cover



Article information

Item no.: 48558.11
 GTIN: 4026092034408
 Price group: 40

Advantages

- High-tech Ecoguss composite material
- Ecoguss, highest fire protection standards
- Scientifically confirmed sound protection effect

Description

The Ecoguss floor/roof drain is used for point drainage and is equipped with a glued flange, a removable odour trap, a lip seal and a temporary protective cover. The recyclable composite material Ecoguss fulfils the highest sound protection requirements, is resistant to aggressive media, temperature resistant and has a permanently corrosion-free surface. It can be exposed to flames of 100 up to 400 degrees Celsius for short periods. The glued flange with a flange width of 50 mm is suitable for connecting waterproofing layers in accordance with DIN 18534, for all waterproofing classes. The loose flange is used for clamping polymer and elastomer sealing sheets as well as for cold bitumen seals and is therefore only suitable for use with moisture barriers. The outlet socket is suitable for connection to SML cast iron pipes. Separate equipotential bonding is not necessary.

Variant

| | |
|---|--|
| System: | 125 |
| Waterproofing layer on the upper section: | Connection flange |
| Waterproofing layer on the drain body: | Adhesive flange (suitable for moisture barriers) |
| Water supply: | W3-I |
| Sealing water height: | 50 mm |

General characteristics

| | |
|----------------------|-----------|
| Standard: | EN 1253-1 |
| Nominal size (DN): | 50 |
| Outer diameter (OD): | 58 mm |

Dimensions

| | |
|----------------------|-------------------------------------|
| Net weight: | 2,02 kg |
| Gross weight: | 2,65 kg |
| Diameter: | 348 mm |
| Vertical adjustment: | vertically adjustable upper section |
| Length: | 348 mm |
| Width: | 348 mm |
| Packaging dimension: | length |
| Packaging dimension: | width |
| Packaging dimension: | height |

| | |
|-------------------------|---------|
| Tank/drain body | |
| Number of outlets: | 1 |
| Material of drain body: | Ecoguss |
| System: | lateral |

Coverage features

| | |
|-------------------------|-----------------------|
| Type of cover: | Slotted cover |
| Cover material: | Stainless steel 14301 |
| Colour of cover: | silver |
| Width of cover: | 138 mm |
| Length of cover: | 138 mm |
| Surface: | Polished SST |
| Frame material: | ABS |
| Cover locking: | screwed |
| Load class: | K 3 (EN 1253-1) |
| Rim length: | 150 mm |
| Rim material: | 150 mm |
| Max. flooring height: | 25 mm |
| Upper section: | vertically adjustable |
| Shape of upper section: | square |
| Upper section material: | ABS |
| Odour trap: | included |