



Ecoguss project drain, press. fl. DN 80, horizontal, Design cover



Article information

Item no.: 48783.63
GTIN: 4026092033463
Discount group: 01

Advantages

- Scientifically confirmed sound protection effect
- Highest fire protection standards

Description

The Ecoguss project drain is used for point drainage and is equipped with a pressure sealing flange as well as a removable odour trap, a lip seal and a temporary protective cover.

The recyclable composite material Ecoguss meets the highest noise protection requirements, is temperature-resistant, resistant to aggressive media, and has a permanently corrosion-free surface. It is also briefly flammable from 100 to 400 degrees Celsius.

The pressure sealing flange with bolts and screws made of stainless steel is used for the clamping or welding of bitumen and polymer bitumen sheets as well as for polymer and elastomer sealing sheets. Only the sealing sheets tested by the manufacturer may be used for watertight seals. The outlet socket is suitable for connection to SML cast iron pipes. Separate equipotential bonding is not necessary.

Version:

| | |
|---|---|
| System: | 125 |
| Odour trap: | included |
| Waterproofing layer on the upper section: | Connection flange |
| Waterproofing layer on the drain body: | Press sealing flange (suitable for creating watertight seals) |
| Sealing water height: | 50 mm |

General characteristics:

| | |
|----------------------|-----------|
| Nominal size (DN): | 80 |
| Outer diameter (OD): | 83 |
| Standard: | EN 1253-1 |

Dimensions:

| | |
|---------|--------|
| Length: | 273 mm |
| Width: | 273 mm |

Tank:

| | |
|--------------------|------|
| Number of outlets: | 1 ST |
|--------------------|------|

Drain body:

| | |
|--|--|
| Material of drain body: | Ecoguss |
| Socket version: | lateral |
| Vertical adjustment: Upper section: | vertically adjustable upper section vertically adjustable |

Coverage features:

| | |
|------------------|---------------------|
| Type of cover: | Design cover |
| Grating design: | Kessel |
| Cover material: | 304 stainless steel |
| Colour of cover: | silver |

| | |
|-----------------------|------------------|
| Max. flooring height: | 16 mm |
| Load class: | L 15 (EN 1253-1) |
| Length: | 120 mm |
| Width: | 120 mm |
| Surface: | ground |
| Locking: | Lock & Lift |

Grating:

| | |
|---------------|---------------------|
| Rim length: | 132 mm |
| Rim width: | 132 mm |
| Rim material: | 304 stainless steel |

| | |
|-------------------------|--------|
| Shape of upper section: | square |
| Upper section material: | ABS |