


Ecoguss project drain, press. fl. DN 50, vertical, Slotted cover





Article information

Item no.: 48858.11 GTIN: 4026092034521

Price group: 40

Advantages

- Scientifically confirmed sound protection effect
- Highest fire protection standards

Description

The Ecoguss project drain is used for point drainage and is equipped with a pressure sealing flange as well as a removable odour trap, a lip seal and a temporary protective cover. The recyclable composite material Ecoguss meets the highest noise protection requirements, is temperature-resistant, resistant to aggressive media, and has a permanently corrosion-free surface. It is also briefly flammable from 100 to 400 degrees Celsius. The pressure sealing flange with bolts and screws made of stainless steel is used for the clamping or welding of bitumen and polymer bitumen sheets as well as for polymer and elastomer sealing sheets. Only the sealing sheets tested by the manufacturer may be used for watertight seals. The outlet socket is suitable for connection to SML cast iron pipes. Separate equipotential bonding is not necessary.

Variant

System: 125

Waterproofing layer on the upper section: Connection flange

Waterproofing layer on the drain body: Press sealing flange (suitable for creating

watertight seals)

Sealing water height: 50 mm

General characteristics

Standard: EN 1253-1

Nominal size (DN): 50 Outer diameter (OD): 58 mm

Dimensions



Net weight: 2,87 kg
Gross weight: 3,5 kg
Diameter: 273 mm

Vertical adjustment: vertically adjustable upper section

Width: 273 mm
Length: 273 mm
Packaging dimension: width
Packaging dimension: height
Packaging dimension: length

Tank/drain body

Number of outlets: 1

Material of drain body: Ecoguss System: vertical

Coverage features

Type of cover: Slotted cover

Cover material: Stainless steel 14301

Colour of cover:silverWidth of cover:138 mmLength of cover:138 mmFrame material:ABSCover locking:screwed

Load class: K 3 (EN 1253-1)

Rim length: 150 mm
Rim material: 150 mm
Max. flooring height: 25 mm

Upper section: vertically adjustable

Shape of upper section: square
Upper section material: ABS
Odour trap: included