

Linearis Comfort upper section L: 950 mm, System 125, WaD, K 3



Article information

Item no.: 48930M GTIN: 4026092079065

Price group: 10

Advantages

- Individual design with reversible stainless steel insert
- Highest fire protection standards
- Low installation depth

Description

Used in combination with a drain body of the KESSEL 125 modular system, the Linearis Comfort upper section is suitable for use as indoor linear drainage.

Variant

System: 125 SonicControl: open

Waterproofing layer on the upper section: Factory-fitted sealing collar (WaD) according to DIN

18534

Water supply: W3-I
Sealing water height: 50 mm
Discharge rate (l/s) with 10 mm backwater: 1,1
Discharge rate (l/s) without backwater: 1 mm

General characteristics

Nominal size (DN): 125 Outer diameter (OD): 125 mm

Dimensions

Net weight: 3,91 kg Gross weight: 4,62 kg Outer dimension, length: 1015 mm Installation depth: 80 - 140 mm Width: 243 mm 115 mm Height: Packaging dimension: width Packaging dimension: height Packaging dimension: length

Coverage features

Type of cover: Stainless steel cover



Cover material: Stainless steel 14301

Colour of cover: silver

Frame material: Stainless steel 14301

Cover locking: placed

Load class: K 3 (EN 1253-1)
Grating colour: optionally tileable

Rim length: 66 mm
Rim material: 950 mm
Upper section material: ABS
Odour trap: included