


Light liquid trap DN 100, slot grat., with backw. Prot-





Article information

Item no.: 52101

GTIN: 4026092029770

Price group: 10

Advantages

- Blocks the path of light liquids in the event of an accident/emergency
- Including odour trap

Description

The light liquid trap made of polymer is suitable for floor slab installation and is equipped with an odour trap and a sludge bucket. The upper section with slotted grating is vertically adjustable.

Variant

Contents of sludge trap:

Sealing water height:

Discharge rate (l/s) with 20 mm threshold:

Mechanical backwater flaps:

yes

50 mm

1

Mechanical backwater flaps:

General characteristics

Standard:EN 13564Nominal size (DN):100Outer diameter (OD):110 mmBackwater protection:Type 5Odour trap:included

Dimensions

Vertical adjustment:30 - 90 mmNet weight:2,55 kgGross weight:2,88 kgCutout dimension, width:250 mmCutout dimension, length:400 mmInstallation depth:216 - 276 mm

Type of height adjustability: vertically adjustable upper section



Length:320 mmWidth:243 mmPackaging dimension:lengthPackaging dimension:widthPackaging dimension:height

Tank/drain body

Material of drain body: Polymer

Coverage features

Type of cover:

Cover material:

Colour of cover:

Width of cover:

Length of cover:

Slotted cover

Polymer

black

188 mm

188 mm

Load class: K 3 (EN 1253-1) Rim width: 200 mm

Rim Wath: 200 mm
Rim length: 200 mm
Shape of upper section: square
Upper section material: Polymer
Contents of sludge trap: yes