


Ferrofix floor/roof drain DN 70, horiz., slot grat., st st



Article information

Item no.: 54400.20
 GTIN: 4026092056448
 Price group: 70

Advantages

- Made of particularly hygienic and mechanically highly resistant stainless steel
- High flow rate

Description

The Ferrofix stainless steel floor drain is used for point drainage and is equipped with a removable odour trap made of stainless steel, a lip seal and a temporary protective cover. The outlet socket is suitable for connection to SML cast iron pipes.

Variant

| | |
|---|-------------------|
| System: | 125 |
| Waterproofing layer on the upper section: | Connection flange |
| Waterproofing layer on the drain body: | Connection flange |
| Sealing water height: | 50 mm |

General characteristics

| | |
|----------------------|-----------|
| Standard: | EN 1253-1 |
| Nominal size (DN): | 70 |
| Outer diameter (OD): | 78 mm |

Dimensions

| | |
|----------------------|-------------------------------------|
| Net weight: | 3,17 kg |
| Gross weight: | 3,69 kg |
| Vertical adjustment: | vertically adjustable upper section |
| Width: | 142 mm |
| Length: | 181 mm |
| Packaging dimension: | width |
| Packaging dimension: | height |
| Packaging dimension: | length |

| | |
|-------------------------|-----------------------|
| Tank/drain body | |
| Number of outlets: | 1 |
| Material of drain body: | Stainless steel 14301 |
| System: | lateral |

Coverage features

| | |
|-------------------------|-----------------------|
| Type of cover: | Slotted cover |
| Cover material: | Stainless steel 14301 |
| Width of cover: | 138 mm |
| Length of cover: | 138 mm |
| Cover locking: | unlocked |
| Load class: | L 15 (EN 1253-1) |
| Rim length: | 150 mm |
| Rim material: | 150 mm |
| Upper section: | vertically adjustable |
| Upper section material: | Stainless steel 14301 |
| Odour trap: | included |