

## Ferrofix floor drain DN 70, horizontal, Slotted grating



### Article information

Item no.: 54400.61  
GTIN: 4026092056523  
Discount group: 03

### Advantages

- Made of particularly hygienic and mechanically highly resistant stainless steel

### Description

The Ferrofix stainless steel floor drain is used for point drainage and is equipped with a removable odour trap made of stainless steel, a lip seal and a temporary protective cover.

The outlet socket is suitable for connection to SML cast iron pipes.

### Version:

System:	125
Odour trap:	included
Waterproofing layer on the upper section:	Connection flange
Waterproofing layer on the drain body:	Connection flange
Sealing water height:	50 mm

### General characteristics:

Nominal size (DN):	70
Outer diameter (OD):	78
Standard:	EN 1253-1

### Dimensions:

Length:	181 mm
Width:	142 mm

### Tank:

Number of outlets:	1 ST
--------------------	------

**Drain body:**

Material of drain body:	Stainless steel 14301
Socket version:	lateral
Vertical adjustment:	vertically adjustable upper section
Upper section:	vertically adjustable

**Coverage features:**

Type of cover:	Slotted cover
Cover material:	Stainless steel 14301
Load class:	L 15 (EN 1253-1)
Length:	138 mm
Width:	138 mm
Locking:	screwed

**Grating:**

Rim length:	150 mm
Rim width:	150 mm
Upper section material:	ABS