


Ferrofix floor/roof drain DN 100, vertical, Slotted grating, SST



Article information

Item no.: 54430.20
GTIN: 4026092056479
Price group: 70

Advantages

- Made of particularly hygienic and mechanically highly resistant stainless steel
- High flow rate

Description

The Ferrofix stainless steel floor drain is used for point drainage and is equipped with a removable odour trap made of stainless steel, a lip seal and a temporary protective cover. The outlet socket is suitable for connection to SML cast iron pipes.

Variant

System:

Waterproofing layer on the upper section:

Waterproofing layer on the drain body:

Sealing water height:

125

Connection flange

Connection flange

50 mm

General characteristics

Standard:

Nominal size (DN):

Outer diameter (OD):

Approval:

EN 1253-1

100

110 mm

Z-19.53-2414,Z-19.53-2414_V,Z-19.17-1719,Z-19.17-1719_V

Odour trap:

included

Dimensions

Net weight:

Gross weight:

Type of height adjustability:

Length:

Width:

3,36 kg

3,71 kg

vertically adjustable upper section

142 mm

142 mm

| | |
|-------------------------|-----------------------|
| Packaging dimension: | length |
| Packaging dimension: | width |
| Packaging dimension: | height |
| Tank/drain body | |
| Number of outlets: | 1 |
| Material of drain body: | Stainless steel 14301 |
| Socket version: | vertical |
| Coverage features | |
| Type of cover: | Slotted cover |
| Cover material: | Stainless steel 14301 |
| Width of cover: | 138 mm |
| Length of cover: | 138 mm |
| Locking: | unlocked |
| Load class: | L 15 (EN 1253-1) |
| Rim width: | 150 mm |
| Rim length: | 150 mm |
| Upper section: | vertically adjustable |
| Upper section material: | Stainless steel 14301 |