


## Ferrofix floor drain press, fl. DN 100, vertical, Slotted grating, SST



### Article information

Item no.: 54430.20  
 GTIN: 4026092056479  
 Price group: 70

### Advantages

- Made of particularly hygienic and mechanically highly resistant stainless steel
- High flow rate

### Description

The Ferrofix stainless steel floor drain is used for point drainage and is equipped with a removable odour trap made of stainless steel, a lip seal and a temporary protective cover. The outlet socket is suitable for connection to SML cast iron pipes.

#### Variant

System:	125
Waterproofing layer on the upper section:	Connection flange
Waterproofing layer on the drain body:	Connection flange
Sealing water height:	50 mm

#### General characteristics

Standard:	EN 1253-1
Nominal size (DN):	100
Outer diameter (OD):	110 mm

#### Dimensions

Net weight:	3,36 kg
Gross weight:	3,71 kg
Vertical adjustment:	vertically adjustable upper section
Width:	142 mm
Length:	142 mm
Packaging dimension:	width
Packaging dimension:	height
Packaging dimension:	length

Tank/drain body	
Number of outlets:	1
Material of drain body:	Stainless steel 14301
System:	vertical

#### Coverage features

Type of cover:	Slotted cover
Cover material:	Stainless steel 14301
Width of cover:	138 mm
Length of cover:	138 mm
Cover locking:	unlocked
Load class:	L 15 (EN 1253-1)
Rim length:	150 mm
Rim material:	150 mm
Upper section:	vertically adjustable
Upper section material:	Stainless steel 14301
Odour trap:	included