# Ferrofix upper section Sys 125, Slotted grating, 200 x 200 mm



## Article information

Item no.: 54916
GTIN: 4026092072455
Price group: 70

## Advantages

- Made of a particularly hygienic and mechanically highly resistant stainless steel
- Multiple combinations with suitable drain bodies

## Description

Used in combination with a drain body of the KESSEL modular system 125, the stainless steel upper section is suitable for indoor point drainage.

| | |
|---|---|
| Variant | |
| System: | 125 |
| Note on installation depth: | For load class M 125, on-site shimming necessary |
| Waterproofing layer on the upper section: | Connection flange |
| | |
| General characteristics | |
| Standard: | EN 1253-1 |
| | |
| Dimensions | |
| Net weight: | 1,92 kg |
| Gross weight: | 2,02 kg |
| Height: | 100 mm |
| Packaging dimension: | width |
| Packaging dimension: | height |
| Packaging dimension: | length |
| | |
| Coverage features | |
| Type of cover: | Slotted cover |
| Cover material: | Stainless steel 14301 |
| Height of cover: | 28 mm |
| Surface: | pickled |
| Cover locking: | unlocked |
| Load class: | L 15 / M 125 (EN 1253-1) |
| Rim length: | 200 mm |
| Rim material: | 200 mm |
| Shape of upper section: | square |
| Upper section material: | Stainless steel 14301 |

| | |
|---|---|
| Mesh size: | 23 x 23 mm |