

Ferrofix upper section Sys125, GI fl., Slot cover, 146x146 mm



Article information

Item no.: 54919
GTIN: 4026092072424
Price group: 70

Advantages

- Made of a particularly hygienic and mechanically highly resistant stainless steel
- Multiple combinations with suitable drain bodies

Description

Used in combination with a drain body of the KESSEL modular system 125, the stainless steel upper section is suitable for indoor point drainage. The upper section is suitable for thin-layered floorings (e.g. epoxy resin) and has a circumferential adhesive joint edge (15 mm deep and 50 mm folded outwards).

Variant	
System:	125
Waterproofing layer on the upper section:	Adhesive flange (suitable for moisture barriers)
Dimensions	
Net weight:	2,09 kg
Gross weight:	2,09 kg
Width:	246 mm
Height:	100 mm
Length:	246 mm
Packaging dimension:	width
Packaging dimension:	height
Packaging dimension:	length
Coverage features	
Type of cover:	Slotted cover
Cover material:	Stainless steel 14301
Height of cover:	15 mm
Surface:	Polished SST
Cover locking:	screwed
Load class:	K 3 (EN 1253-1)
Rim length:	146 mm
Rim material:	146 mm
Shape of upper section:	square
Upper section material:	Stainless steel 14301