


Ferrofix upper section glue flange H: 6mm, 200x200mm, slot grat.



Article information

Item no.: 54928
GTIN: 4026092099896
Price group: 70

Advantages

- Made of a particularly hygienic and mechanically highly resistant stainless steel
- Multiple combinations with suitable drain bodies

Description

Used in combination with a drain body of the KESSEL modular system 125, the stainless steel upper section is suitable for indoor point drainage. The upper section is suitable for thin-layered floorings (e.g. epoxy resin) and has a circumferential adhesive joint edge (6 mm deep and 50 mm folded outwards).

Variant

System:	125
Note on installation depth:	For load class M 125, on-site shimming necessary
Waterproofing layer on the upper section:	Adhesive flange (suitable for moisture barriers)
Water exposure class in accordance to DIN 18534-1 (up to and including):	W3-I

Dimensions

Net weight:	4,04 kg
Gross weight:	4,39 kg
Length:	300 mm
Width:	300 mm
Height:	110 mm
Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height

Coverage features

Type of cover:	Slotted cover
----------------	---------------

Width of cover:	200 mm
Height of cover:	6 mm
Length of cover:	200 mm
Surface:	pickled
Locking:	placed
Load class:	L 15 / M 125 (EN 1253-1)
Shape of upper section:	square
Upper section material:	Stainless steel 14301
Mesh size:	23 x 23 mm