


## Ferrofix upper section Gl. flange H:15mm, 300x300mm,insert, L15



### Article information

Item no.: 55137  
 GTIN: 4026092107621  
 Price group: 70

### Advantages

- Made of a particularly hygienic and mechanically highly resistant stainless steel
- Multiple combinations with suitable drain bodies

### Description

Used in combination with a drain body of the KESSEL modular system 185, the stainless steel upper section is suitable for indoor point drainage. The upper section is suitable for thin-layered floorings (e.g. epoxy resin) and has a circumferential adhesive joint edge (15 mm deep and 50 mm folded outwards).

Variant	
System:	185
Waterproofing layer on the upper section:	Adhesive flange (suitable for moisture barriers)

General characteristics	
Standard:	EN 1253-1

Dimensions	
Net weight:	10,4 kg
Gross weight:	10,4 kg
Length:	300 mm
Width:	300 mm
Height:	200 mm
Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height

Coverage features	
Type of cover:	Ladder grating

Cover material:	Stainless steel 14301
Height of cover:	15 mm
Locking:	unlocked
Load class:	L 15 (EN 1253-1)
Grating material:	304 stainless steel
Shape of upper section:	square
Upper section material:	Stainless steel 14301
Cover	
Grating material:	304 stainless steel