

## Ferrofix upper section gl. flange Sys200, slot grat, 304SST, 200 x 200 mm



### Article information

Item no.: 57410-KF  
GTIN: 4026092093283  
Price group: 70

### Advantages

- Made of a particularly hygienic and mechanically highly resistant stainless steel
- Multiple combinations with suitable drain bodies

### Description

Used in combination with a drain body of the KESSEL modular system 200, the Ferrofix stainless steel upper section with glued flange is suitable for indoor point drainage.

#### Variant

System:	200
Waterproofing layer on the upper section:	Adhesive flange (suitable for moisture barriers)
Water exposure class in accordance to DIN 18534-1 (up to and including):	W3-I

#### Dimensions

Net weight:	3,11 kg
Gross weight:	3,62 kg
Type of height adjustability:	vertically adjustable upper section
Length:	300 mm
Width:	300 mm
Height:	110 mm
Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height

#### Coverage features

Type of cover:	Slotted cover
Cover material:	Stainless steel 14301
Height of cover:	15 mm
Locking:	unlocked
Load class:	L 15 (EN 1253-1)
Rim width:	200 mm
Rim length:	200 mm

Upper section material:  
Mesh size:

Stainless steel 14301  
23 x 23 mm