

Ferrofix upper section gl. flange Sys 200, Ladd grt, 304 SST, 200 x 200 mm



Article information

Item no.: 57420-KF
 GTIN: 4026092102992
 Price group: 70

Advantages

- Made of a particularly hygienic and mechanically highly resistant stainless steel
- Multiple combinations with suitable drain bodies

Description

Used in combination with a drain body of the KESSEL modular system 200, the Ferrofix stainless steel upper section with glued flange is suitable for indoor point drainage.

Variant	
System:	200
Waterproofing layer on the upper section:	Adhesive flange (suitable for moisture barriers)
Water exposure class in accordance to DIN 18534-1 (up to and including):	W3-I

Dimensions	
Net weight:	4,51 kg
Gross weight:	4,62 kg
Type of height adjustability:	vertically adjustable upper section
Length:	300 mm
Width:	300 mm
Height:	110 mm
Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height

Coverage features	
Type of cover:	Ladder grating
Cover material:	Stainless steel 14301
Height of cover:	15 mm
Locking:	unlocked
Load class:	L 15 (EN 1253-1)
Rim width:	200 mm
Rim length:	200 mm

Upper section material:

Stainless steel 14301