


## Box channel Ferrofix glued flange H: 15mm, 200x2050mm



### Article information

Item no.: 6020200  
GTIN: 4026092098615  
Price group: 80

### Advantages

- Made of particularly a hygienic and mechanically highly resistant stainless steel
- Variably combinable with suitable drain bodies

### Description

The Ferrofix box channel made of stainless steel with a material thickness of 2.0 mm (pickled in the immersion bath) is equipped with polished visible ridges, longitudinal and transverse slopes, feet for height adjustment and stainless steel outlet nozzles. The channel profile is suitable for joint sealing and has a circumferential adhesive edge (15 mm deep and 50 mm folded outwards) with welded mitres. The glued flange is suitable for connecting waterproofing layers in accordance with DIN 18534, for all waterproofing classes.

#### Variant

Waterproofing layer on the upper section:  
Water exposure class in accordance to DIN 18534-1 (up to and including):

Adhesive flange (suitable for moisture barriers)  
W3-I

#### General characteristics

Nominal size (DN):	125
Outer diameter (OD):	125 mm
Glued flange height:	15 mm

#### Dimensions

Net weight:	23 kg
Gross weight:	23 kg
Length:	2050 mm
Width:	200 mm
Height:	60 mm

Coverage features

Type of cover:

Colour of cover:

Locking:

Load class:

Slip resistance class:

Upper section material:

Slotted cover

silver

placed

L 15 (EN 1253-1)

R12 according to DIN 51130; C according to DIN 51097

Stainless steel 14301