


Floor Tray Ferrofix glued flange H: 6mm, 500x500mm



Article information

Item no.: 6250050
 GTIN: 4026092099322
 Price group: 80

Advantages

- Made of particularly a hygienic and mechanically highly resistant stainless steel
- Variably combinable with suitable drain bodies

Description

The Ferrofix floor tray made of stainless steel with a material thickness of 1.5 mm (pickled in the immersion bath) is equipped with ground crosspieces, longitudinal and transverse gradients, feet for height adjustment and stainless steel outlet nozzles. The channel profile is suitable for thin-layered floorings (e.g. epoxy resin) and has an all-round adhesive rim (6 mm deep and 50 mm folded outwards) with welded mitres. The glued flange is also suitable for connecting waterproofing.

Variant

Waterproofing layer on the upper section: Adhesive flange (suitable for moisture barriers)

General characteristics

Nominal size (DN): 125
 Outer diameter (OD): 125 mm
 Glued flange height: 6 mm

Dimensions

Net weight: 13,2 kg
 Gross weight: 13,2 kg
 Length: 500 mm
 Width: 500 mm
 Height: 60 mm
 Packaging dimension: length
 Packaging dimension: width
 Packaging dimension: height

Coverage features

Type of cover:

Colour of cover:

Locking:

Load class:

Slip resistance class:

Upper section material:

Slotted cover

silver

placed

L 15 (EN 1253-1)

R12 according to DIN 51130; C according to DIN 51097

Stainless steel 14301