

Replacement pump, Pumpfix F DN 150, 15 m cable



Article information

Item no.: 680042
GTIN: 4026092062357
Price group: 90

Description

Replacement pump with cover, motor, impeller, blades and pump housing for faecal wastewater

Variant

Pump control:

Control unit

General characteristics

Standard:

EN 12050-1

Type of wastewater:

with sewage

Dimensions

Net weight:

16 kg

Gross weight:

16 kg

Packaging dimension:

length

Packaging dimension:

width

Packaging dimension:

height

Pumping device

Pump:

SPZ 1000

Connection type:

Schuko (earthed contact) 2-pin

Operating voltage:

230 V

Mains frequency:

50 Hz

Protection class:

I

Insulation class:

F

Cos phi - power factor:

0,97

Protection class (pump):

IP 68 (3m/48h)

Temperature monitoring:

integrated

Max. temperature (permanent) of conveyed material:

35 °C

Max. pumping height:

10 m

Speed:

2800 U/min

Power P1:

1,2 kW

Power P2:

0,7 kW

Operating mode:	S3 - 30 %
Type of pump connection cable:	H07RN-F 3G 1.5 mm ²
Impeller type:	Macerator
Length of mains cable for pump:	15 m
Rated current:	5,2 A
Control	
Operating voltage:	230 V
Connection type:	Schuko (earthed contact) 2-pin
Type of fuse required (electrical protection):	C 16 A