

Replacement pump, Pumpfix F DN 150, 15 m cable



Article information

Item no.: 680042
GTIN: 4026092062357
Price group: 90

Description

Replacement pump with cover, motor, impeller, blades and pump housing for faecal wastewater

Variant	
Pump control:	Control unit
General characteristics	
Standard:	EN 12050-1
Type of wastewater:	with sewage
Dimensions	
Net weight:	16 kg
Gross weight:	16 kg
Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height
Pumping device	
Pump:	SPZ 1000
Connection type:	Schuko (earthed contact) 2-pin
Operating voltage:	230 V
Mains frequency:	50 Hz
Protection class:	I
Insulation class:	F
Cos phi - power factor:	0,97
Protection class (pump):	IP 68 (3m/48h)
Temperature monitoring:	integrated
Max. temperature (permanent) of conveyed material:	35 °C
Max. pumping height:	10 m
Speed:	2800 U/min
Power P1:	1,2 kW
Power P2:	0,7 kW

Operating mode:	S3 - 30 %
Type of pump connection cable:	H07RN-F 3G 1.5 mm ²
Impeller type:	Macerator
Length of mains cable for pump:	15 m
Rated current:	5,2 A
Control	
Operating voltage:	230 V
Connection type:	Schuko (earthed contact) 2-pin
Type of fuse required (electrical protection):	C 16 A