

Replacement pump TPF 154 400 V, 1.9 kW



Article information

Item no.: 680411
GTIN: 4026092069660
Price group: 90

Description

Replacement pump with macerator for faecal wastewater, includes connection adapter for TPF154

Variant

Series: bis 10/2006

General characteristics

Standard: EN 12050-1
Type of wastewater: with sewage

Dimensions

Net weight: 53,9 kg
Gross weight: 53,9 kg
Packaging dimension: length
Packaging dimension: width
Packaging dimension: height

Pumping device

Pump: TPF 154
Weight, pump: 47 kg
Connection type: Direct connection
Operating voltage: 400 V
Mains frequency: 50 Hz
Protection class: I
Insulation class: F
Cos phi - power factor: 0,83
Protection class (pump): IP 68
Temperature monitoring: controlled via control unit
Max. temperature (permanent) of conveyed material: 40 °C
Max. pumping height: 32 m
Speed: 2885 U/min
Power P1: 2,6 kW

Power P2:	1,9 kW
Operating mode:	S1
Type of pump connection cable:	H07RN-F 7G 1.5 mm ²
Type of fuse required (pump):	Fuse protection through control unit 400 V
Length of mains cable for pump:	10 m
Rated current:	4,5 A
Control	
Connection type:	Direct connection