

Replacement pump pumping station dry installation SPF 4500-S3



Article information

Item no.: 680533
 GTIN: 4026092074947
 Price group: 90

Description

Replacement pump type SPF 4500-S3 for Aqualift F XL pumping station, dry installation

Variant

Rim width: Control unit

General characteristics

Cable length: 10 m

Dimensions

Net weight: 26,5 kg

Gross weight: 29,3 kg

Packaging dimension: width

Packaging dimension: height

Packaging dimension: length

Pumping device

Pump control: SPF 4500

Connection type: Direct connection

Rated current: 7,5 A

Length of mains cable for pump: 10 m

Self-diagnosis system (SDS): I

Insulation class: F

Cos phi - power factor: 0,85

Protection class control unit: IP 68

DSC: controlled via control unit

Max. temperature (permanent) of conveyed material: 40 °C

Max. pumping height: 20 m

Speed: 2850 U/min

Power P1: 4,2 kW

Power P2: 3,5 kW

Operating mode: S3 - 50 %

Type of fuse required (electrical protection):
Type of pump connection cable:

Fuse protection through control unit 400 V
H07RN-F 7G 1.5 mm²

Control

Mains frequency:

50 Hz

Operating voltage:

400 V

Connection type:

Direct connection