

Replacement pump pumping station dry installation SPF 4500-S1



Article information

Item no.: 680534
 GTIN: 4026092074954
 Price group: 90

Description

Replacement pump type SPF 4500-S1 for Aqualift FXL pumping station, dry installation

Variant	
Pump control:	Control unit
General characteristics	
Cable length:	10 m
Dimensions	
Net weight:	33,2 kg
Gross weight:	36 kg
Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height
Pumping device	
Pump:	SPF 4500-S1
Connection type:	Direct connection
Operating voltage:	400 V
Mains frequency:	50 Hz
Protection class:	I
Insulation class:	F
Cos phi - power factor:	0,85
Protection class (pump):	IP 68
Max. temperature (permanent) of conveyed material:	40 °C
Max. pumping height:	20 m
Speed:	2850 U/min
Power P1:	4,2 kW
Power P2:	3,5 kW
Operating mode:	S3 - 50 %
Type of pump connection cable:	H07RN-F 7G 1.5 mm²

Type of fuse required (pump):
Length of mains cable for pump:
Rated current:

Fuse protection through control unit 400 V
10 m
7,5 A

Control
Operating voltage:
Connection type:

400 V
Direct connection