

## Replacement pump Aquadive GTF1200 with float switch, 10 m



### Article information

Item no.: 680594  
GTIN: 4026092078808  
Price group: 90

### Description

Replacement pump, Aquadive GTF 1200 with floater for pumping station

Variant	
Rim width:	Float switch
General characteristics	
Cable length:	10 m
Dimensions	
Net weight:	11,44 kg
Gross weight:	11,44 kg
Packaging dimension:	width
Packaging dimension:	height
Packaging dimension:	length
Pumping device	
Pump control:	GTF 1200
Connection type:	Schuko (earthed contact) 2-pin
Rated current:	6,2 A
Length of mains cable for pump:	10 m
Self-diagnosis system (SDS):	I
Insulation class:	F
Cos phi - power factor:	0,98
Protection class control unit:	IP 68
Max. temperature (permanent) of conveyed material:	35 °C
Max. pumping height:	9 m
Speed:	2650 U/min
Power P1:	1,4 kW
Power P2:	0,84 kW
Operating mode:	S3 - 50 %
Type of fuse required (electrical protection):	C 16 A
Type of pump connection cable:	H07RN-F 3G 1.5 mm²

Control

Mains frequency:

50 Hz

Operating voltage:

230 V

Connection type:

Schuko (earthed contact) 2-pin