

Replacement pump Aquadive GTF1200 without float switch, 10 m



Article information

Item no.: 680595
GTIN: 4026092078815
Price group: 90

Description

Replacement pump, Aquadive GTF 1200 without floater for pumping station

Variant	
Rim width:	Control unit
General characteristics	
Cable length:	10 m
Dimensions	
Net weight:	11,19 kg
Gross weight:	11,19 kg
Packaging dimension:	width
Packaging dimension:	height
Packaging dimension:	length
Pumping device	
Pump control:	GTF 1200
Connection type:	Schuko (earthed contact) 2-pin
Rated current:	6,2 A
Length of mains cable for pump:	5 m
Self-diagnosis system (SDS):	I
Insulation class:	F
Cos phi - power factor:	0,98
Protection class control unit:	IP 68
DSC:	integrated
Max. temperature (permanent) of conveyed material:	35 °C
Max. pumping height:	9 m
Speed:	2650 U/min
Power P1:	1,4 kW
Power P2:	0,84 kW
Operating mode:	S1
Type of fuse required (electrical protection):	Fuse protection through control unit 230 V

Type of pump connection cable:

H07RN-F 3G 1.5 mm²

Control

Mains frequency:

50 Hz

Operating voltage:

230 V

Connection type:

Schuko (earthed contact) 2-pin