

Replacem. pump Aquadive STZ 1300 without float switch, 10 m, ATEX



Article information

Item no.: 680604
 GTIN: 4026092078488
 Price group: 90

Description

Replacement pump, Aquadive STZ 1300, ATEX, without float, for pumping station, wet installation

Variant	
Pump control:	Control unit
General characteristics	
Cable length:	10 m
Dimensions	
Net weight:	27 kg
Gross weight:	30 kg
Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height
Pumping device	
Pump:	STZ 1300
Weight, pump:	27 kg
Connection type:	Direct connection
Operating voltage:	400 V
Mains frequency:	50 Hz
Protection class:	I
Insulation class:	H
Cos phi - power factor:	0,8
Protection class (pump):	IP 68
Max. temperature (permanent) of conveyed material:	40 °C
Max. pumping height:	21 m
Speed:	2900 U/min
Power P1:	1,3 kW

Power P2:	0,9 kW
Operating mode:	S1
Type of pump connection cable:	H07RN8-F 6G 1.5 mm ²
Impeller type:	Macerator
Type of fuse required (pump):	Fuse protection through control unit 400 V
Length of mains cable for pump:	10 m
Rated current:	2,5 A
Control	
Operating voltage:	400 V
Connection type:	Direct connection