

Replacem. pump Aquadive STZ 3700 without float switch, 10 m, ATEX



Article information

Item no.: 680606
GTIN: 4026092078501
Price group: 90

Description

Replacement pump, Aquadive, STZ 3700, ATEX, without floater, for pumping station, wet installation

| | |
|--|-----------------------------|
| Variant | |
| Pump control: | Control unit |
| General characteristics | |
| Cable length: | 10 m |
| Dimensions | |
| Net weight: | 43 kg |
| Gross weight: | 46 kg |
| Packaging dimension: | length |
| Packaging dimension: | width |
| Packaging dimension: | height |
| Pumping device | |
| Pump: | STZ 3700 |
| Weight, pump: | 44 kg |
| Connection type: | Direct connection |
| Operating voltage: | 400 V |
| Mains frequency: | 50 Hz |
| Protection class: | I |
| Insulation class: | H |
| Cos phi - power factor: | 0,82 |
| Protection class (pump): | IP 68 |
| Temperature monitoring: | controlled via control unit |
| Max. temperature (permanent) of conveyed material: | 40 °C |
| Max. pumping height: | 35 m |
| Speed: | 2900 U/min |

| | |
|---------------------------------|--|
| Power P1: | 3,7 kW |
| Power P2: | 3,1 kW |
| Operating mode: | S1 |
| Type of pump connection cable: | H07RN8-F 6G 1.5 mm ² |
| Impeller type: | Macerator |
| Type of fuse required (pump): | Fuse protection through control unit 400 V |
| Length of mains cable for pump: | 10 m |
| Rated current: | 6,4 A |
| Control | |
| Operating voltage: | 400 V |
| Connection type: | Direct connection |